

**0608E(2132E)/0808E(2732E)**

Complies with ISO/CE/ANSI/CSA/AS/EAC standards

**PRODUCT HIGHLIGHTS****Efficient and environmentally friendly**

- Higher work efficiency
- Environmental protection, zero emissions

**Reduced maintenance costs**

- The short design of sliding rail makes debris easy to clean
- Rapid, convenient transportation with two-way forklift slot
- Lower cost of ownership with highly versatile parts and components

**Reliable performance**

- New wide scissor design, for a more stable working-at-height experience
- Bumper rail and indented sliding rail designed for anti-scratch

**Standard Features**

2WD×2WS	Maintenance-free battery	Fault diagnosis system
Non-marking tires	Proportional control	Emergency lowering system
Emergency stop	Electrophoretic painting	Tilt protection system
Flashing beacon	Forklift pockets and lifting points	Overload sensing system
Foldable guardrail	Automatic pothole protection	Manual storage box
Drivable at full height	Bumper rails	Telematics-ready connector
Horn & buzzer	AC power to platform with RCBO	

**Options & Accessories**

Lithium battery	AC drive motor	Platform work light
Footswitch	Secondary guarding device	

ELECTRIC SERIES SCISSOR LIFTS

# 0608E(2132E)/0808E(2732E)

Complies with ISO/CE/ANSI/CSA/AS/EAC standards

Model	0608E (2132E)	0808E (2732E)
<b>Dimensions</b>		
Max Working Height	8.3m(27'3")	10.1m/ 8m (33'2"/ 26'3") indoor / outdoor
A Max Platform Height	6.3m(20'8")	8.1m/ 6m (26'7"/ 19'8") indoor/outdoor
B Max Horizontal Extension	0.9m(3')	0.9m(3')
C Length-Stowed	2.46m(8')	2.46m(8')
D Width-Stowed	0.83m(2'9")	0.83m(2'9")
E Height-stowed (Rail Folded)	1.84m(6')	1.96m(6'5")
E Height-stowed (Rail Unfolded)	2.24m(7'4")	2.36m(7'9")
F Wheelbase	1.88m(6'2")	1.88m(6'2")
Ground Clearance(Pothole Guard Stowed)	0.1m(4")	0.1m(4")
Ground Clearance(Pothole Guard Deployed)	25mm(0.98")	25mm(0.98")
Platform Dimensions(LxWxH)	2.3m x 0.8m x 1.1m (7'7" x 2'8" x 3'7")	2.30m x 0.8m x 1.1m (7'6.7" x 2'8" x 3'7")
<b>Performance</b>		
Platform Allowable Occupants(Indoor/Outdoor)	2 persons/1 person	2 persons/1 person
Platform Capacity	380kg(838lbs)	250kg(551lbs)
Drive Speed-Stowed	4km/h(2.5mph)	4km/h(2.5mph)
Drive Speed-Raised	0.8km/h(0.5mph)	0.8km/h(0.5mph)
Elevation Time(Unloaded)	25s~30s	30s~35s
Descent Time(Unloaded)	30s~35s	34s~39s
Gradeability	25%	25%
Turning Radius(Inside/Outside)	0/2.1m(0/6'11")	0/2.1m(0/6'11")
Tilt Rating(Front to Back/Side to Side)	3°/1.5°	3°/1.5°
Tyre Spec/Type	380x125mm(15x5')/solid	380x125mm(15x5')/solid
<b>Power</b>		
Batteries	6Vx4/225Ah	6Vx4/225Ah
Power Source	24V DC	24V DC
Drive Mode	Motor, front-wheel	Motor, front-wheel
Charger Input	100-240V AC	100-240V AC
Charger Output	30A	30A
Hydraulic Tank Capacity	15L(3.3gal(UK) / 3.9gal(US))	15L(3.3gal(UK)/ 3.9gal(US))
<b>Weight</b>		
Weight	2,090kg(4,608 lbs)	2,265kg(4,994lbs)
Standards Compliance	ISO/CE/ANSI/CSA/AS/EAC	

