

0608SE(1930SE)/0608ME(1932ME)

Compliance with ISO/CE/ANSI/CSA/AS/EAC standards

PRODUCT HIGHLIGHTS**Efficient and environmentally friendly**

- Higher work efficiency
- Environmental protection and zero emissions

Reduced maintenance costs

- Rapid and convenient transportation with a two-way forklift slot
- Lower cost of ownership with highly versatile parts

Reliable performance

- Bumper rail protection



Standard Features		
2WD×2WS	Maintenance-free battery	Fault diagnosis system
Non-marking tires	Proportional control	Emergency lowering system
Emergency stop	Electrophoretic painting	Tilt protection system
Flashing beacon	Forklift pockets and lifting points	Overload sensing system
Foldable guardrail	Automatic pothole protection	Manual storage box
Drivable at full height	Bumper rails	Telematics-ready connector
Horn & buzzer	AC power to platform with RCBO	
Options & Accessories		
Lithium battery	AC drive motor	Platform work light
Footswitch	Secondary guarding device	

ELECTRIC SERIES SCISSOR LIFTS

0608SE(1930SE)/0608ME(1932ME)

Compliance with ISO/CE/ANSI/CSA/AS/EAC standards

Model	0608SE/0608ME(1930SE/1932ME)
Dimensions	
Max Working Height	7.8m(25'7")
A Max Platform Height	5.8m(19')
B Max Horizontal Extension	0.9m(3')
C Length-Stowed	1.8m(5'11")
D Width-Stowed	0608SE 0.79m(2'7") / 0608ME 0.81m(2'8")
E Height-stowed (Rail Folded)	1.88m(6'2")
E Height-stowed (Rail Unfolded)	2.14m(7')
F Wheelbase	1.33m(4'4")
Ground Clearance(Pothole Guard Stowed)	75mm(3")
Ground Clearance(Pothole Guard Deployed)	24mm(0.95")
Platform Dimensions(LxWxH)	1.64m x 0.76m x 1.1m(5'5" x 2'6" x 3'7")
Performance	
Platform Allowable Occupants(Indoor/Outdoor)	0608SE(2persons/-), 0608ME(2persons/1 person)
Platform Capacity	230kg(507lbs)
Drive Speed-Stowed	4km/h(2.5mph)
Drive Speed-Raised	0.8km/h(0.5mph)
Elevation Time(Unloaded)	15s~20s
Descent Time(Unloaded)	25s~30s
Gradeability	25%
Turning Radius(Inside/Outside)	0/1.49m(0/4'11")
Tilt Rating(Front to Back/Side to Side)	3°/1.5°
Tyre Size/Type	323x100mm(12.7x4")/solid
Power	
Batteries	6Vx4/225Ah
Power Source	24V DC
Drive Mode	Motor, front-wheel
Charger Input	100~240V AC
Charger Output	30A
Hydraulic Tank Capacity	7L(1.54gal(UK)/ 1.85gal(US))
Weight	
Weight	1,575kg(3,473lbs)
Standards Compliance	ISO/CE/ANSI/CSA/AS/EAC

