

## ENGINE POWERED ROUGH TERRAIN SCISSOR LIFTS

# 1323RD (4389RD) / 1623RD (5389RD)

Compliant with CE/ANSI/CSA/AS/EAC standards

## HIGHLIGHTS

### Excellent performance

- Better drive and working performance on rough terrains based on improved chassis and active oscillating function
- Smoother dual slide-out extension platform is available for locking at any positions
- Optimum working efficiency with one button for auto-levelling outriggers

### Easy maintenance

- It provides better access to reach all components installed on two sides of chassis
- Slide-out engine tray makes engine completely accessible
- Quick fault inquiry thanks to on-board diagnostic system



Standard Features		
4 WD × 2 WS	Forklift pockets	Lifting and tie-down points
Document box	Electrophoretic painting	Proportional controls
Emergency stop	Dual slide-out extension platform	Emergency lowering system
Foldable guardrails	Horn & buzzer	Auto braking system
Tilt alarm	Motion alarm	Load sensing system
Drivable at full height (1323RD only)	Flashing beacon	Fault diagnosis system
Active oscillating function	Auto-levelling hydraulic outriggers	Foam-filled non-marking tires
Telematics-ready connector	7.4m platform	AC power to platform
Options & Accessories		
Cold weather package	6.5m platform	

**SINOBOOM™**

**PARTNERS IN ACCESS™**

SINOBOOM.EU | INFO@SINOBOOM.EU | +31 180 225 666  
NIKKELSTRAAT 26, 2984 AM RIDDERKERK, THE NETHERLANDS

# ENGINE POWERED ROUGH TERRAIN SCISSOR LIFTS 1323RD (4389RD) / 1623RD (5389RD)

Compliant with CE/ANSI/CSA/AS/EAC standards

Model	1323RD (4389RD)	1623RD (5389RD)
<b>Dimensions</b>		
Max.Working Height	15.1 m (49'6.5")	18.2 m (59'8.5")
A Max.Platform Height	13.1 m (42'11.7")	16.2 m (53'1.8")
B Platform Extension (Front/Back)	1.5 m/1.2 m (4'11.1"/3'11.2")	
C Overall Length	4.88 m (16')	
D Overall Width	2.31 m (7'7")	
E Height-Stowed (Rails Folded)	2.20 m (7'2.6")	2.42 m (7'11.3")
E Height-Stowed (Rails Unfolded)	2.96 m (9'8.5")	3.18 m (10'5.2")
F Wheelbase	2.85 m (9'4")	
Ground Clearance	0.36 m (1'2.2")	
Platform Size (L×W×H)6.5 m Platform	3.96 m×1.82 m×1.1 m (13'×6'×3'7")	
Platform Size (L×W×H)7.4 m Platform	4.84 m×1.82 m×1.1 m (15'10.6"×6'×3'7")	
<b>Performance</b>		
Platform Capacity	680 kg (1,499 lbs)	
Capacity on Platform Extension	227 kg (500 lbs)	
Max.Platform Occupants (Indoor/Outdoor)	7 Persons/7 Persons	4 Persons/4 Persons
Drive Speed (Stowed)	5.0 km/h (3.1 mph) Kubota engine	
Drive Speed (Raised)	1.1 km/h (0.7 mph)	
Lift Time (Unloaded)	50 s~60 s	70 s~90 s
Lower Time (Unloaded)	34 s~44 s	45 s~55 s
Gradeability	40%	
Tilt Rating (Front-to-Back)	3°	
Tilt Rating (Side-to-Side)	2°	
Max.Outrigger Levelling (Front-to-Back)	7°	
Max.Outrigger Levelling (Side-to-Side)	12°	
Turning Radius (Inside/Outside)	2.2 m/5.3 m (7'2.6"/17'4.7")	
Tire Spec/Type	315/55D20/Foam-Filled	
<b>Power</b>		
Drive × Steer	4WD×2WS	
Engine (Brand/Model/Power/Emissions)	Kubota / D1105 / 18.2 kW(24.7 hp)	
Hydraulic Tank Capacity	107L/23.5 gal(UK)/28 gal(US)	
Fuel Tank Capacity	110L (24 gal (UK)/29gal (US))	
<b>Weight</b>		
Weight (Kubota engine)	7,170 kg (15,807 lbs)	8,000 kg (17,637 lbs)
<b>Standards Compliance</b>		
CE/ANSI/CSA/AS/EAC		

